

Mastic Tape is a cold-applied butyl sealant designed for use with Gala Heat Cable Joint and Termination kits to offer excellent water sealing and weatherproofing.

Black Mastic (HBMT):

Black mastic is suitable for LV and MV applications. It is used for sealing and waterproofing of electrical installations such as joints and terminations, as well as in telecom installations.

Red Mastic (HRMT):

Red mastic is used in MV terminations to ensure a watertight seal on breakout boots, non-tracking tube and on lugs.

Yellow Stress Control Mastic (HSCM):

Stress relief void filling mastic is used on connectors and at screen cuts when doing medium voltage joints and termination installations.


Features & Benefits:

- Excellent adhesive and sealing capability
- Good di-electrical properties
- UV and weather resistance
- Resistant to chemicals

Technical Specification						
PROPERTIES	STANDARD	TYPICAL VALUE				
		Black	Red	Yellow		
Tensile Strength (Mpa)	ASTM D638	0.1 (min.)	0.5 (min.)	0.1 (min.)		
Ultimate Elongation (%)	ASTM D638	300 (min)	300 (min)	300 (min)		
Density (gm/cm³)	ASTM D792	1.30 ± 0.2	1.20 ± 0.2	1.30 ± 0.2		
Service Temp. (°C)	IEC 216	-20 to +90	-20 to +90	-20 to +90		
Di-electric Strength (kV/mm)	ASTM D149	6 (min)	10 (min)	15 (min)		
Volume Resistivity (Ohm.cm)	ASTM D257	1 x 10 ¹⁰ (min)	1 x 10 ¹⁴ (min)	1 x 10° (min)		
Di-electric Constant	ASTM D150	2 - 3	3 (max.)	10 (min.)		
50 Hz Loss Factor		0.035	0.035	0.035		
Adhesive & Self-amalgamation	-	Good	Good	Good		

Selection Chart						
W (Min.) (mm)	L (Min.) (mm)	T (±5%) (mm)	Form			
35	100	2.5	Strips			
35	200	2.5	Strips			
35	300	2.5	Strips			
35	450	2.5	Strips			
35	1000	2.5	Roll			
35	2000	2.5	Roll			
35	150	2.5	Strips			
35	25000	2.5	Roll			
35	400	2.5	Roll			
35	300	2.0	Strips			
35	450	2.0	Strips			
35	25000	1.7	Roll			
35	450	1.7	Strips			
35	300	1.7	Strips			
20	100	1.7	Strips			
25	450	1.7	Strips			
	W (Min.) (mm) 35 35 35 35 35 35 35 35 35 35 35 35 35	W (Min.) (mm) L (Min.) (mm) 35 100 35 200 35 300 35 450 35 2000 35 2000 35 25000 35 400 35 300 35 450 35 450 35 300 20 100	W (Min.) (mm) L (Min.) (mm) T (±5%) (mm) 35 100 2.5 35 200 2.5 35 300 2.5 35 450 2.5 35 2000 2.5 35 2000 2.5 35 25000 2.5 35 400 2.5 35 400 2.5 35 450 2.0 35 25000 1.7 35 450 1.7 35 300 1.7 20 100 1.7			

W: Width, L: Length, T: Thickness





GALA SHRINK FIT